



Parts Details



Ergonomic Handle



PU Wheel



Nylon Wheel



Height Adjustable



Integral Casting Pump Station



Double Bearing Wheel

Specification

Type	PT-2	PT-2.5	PT-3	PT-5	PT5-1
Capacity (kg)	2000	2500	3000	5000	5000
Height when lowered (mm)	85	85	85	85	85
Big wheel size (mm)	Φ180*50	Φ180*50	Φ180*50	Φ180*50	Φ180*50
Double wheel size (mm)	Φ80*70	Φ80*70	Φ80*70	Φ80*70	Φ80*70
Total height (mm)	1224	1224	1224	1224	1224
Total length (mm)	1533/1603	1533/1603	1533/1603	1533	1603
Fork length (mm)	1150/1220	1150/1220	1150/1220	1150	1220
Fork out width (mm)	550/685	550/685	550/685	550	685
Turning radius (mm)	1266/1366	1266/1366	1266/1366	1266	1336
Self-weight (kg)	61.8/65.2	63.8/68.2	65.8/69.2	114	120

Hand Pallet Truck

The Hand pallet truck inserts its cargo fork into the pallet hole when in use. And the hydraulic system is driven by human to realize the lifting and lowering of the pallet cargo. And the handling is completed by human pulling. It is the simplest, most effective and most common loading, unloading and handling tool in pallet transport.

